Pull Type Toroidal Winding Machine

Model PTW-1

Jovil Universal is proud to present the model PTW-1 Pull Type Toroidal Winding Machine. This machine is equipped with a pneumatic cylinder to pull the wire. The core is rotated automatically with the 4 rubber rollers and there is a foot switch to control the cycles.



Features

- Professional hook design which does not damage the wire insulator.
- · Using pneumatic cylinder to pull firmly.
- · Adjustable winding speed.
- Automatic counter for the No. of turns
- Bright LED display
- · Precise potentiometer to adjust the Pitch easily
- Pitch can be adjusted when winding.
- Core is being rotated by 4 rubber rollers.
- · Rotation of the core is more precise
- Machine is operated by footpedal which is easy to use

MAXIMUM

- · Photo-sensor safety light Curtain
- · Choices of 4 hooks

Specification

- Minimum O.D: 15mm
- Maximum O.D: 60mm
- Minimum I.D: 5mm
- Minimum Wire Size: 0.3mm
- Maximum Wire Size: 2.0mm
- · Maximum Core Height: 50mm

Capabilities

	PART NO.		
NEEDLE		WIRE SIZE	
3.2 mm	75B.0021P(A)	0.8 mm	
4.8 mm	75B.0021P(B)	1.2 mm	
6.4 mm	75B.0021P(C)	1.7 mm	
9.5 mm	75B.0021P(D)	2.0 mm	